

C291X/060060

Steel Block Paviour Access Cover, 600mm x 600mm clear opening, 100mm tray depth, Loading code X



CLEAR OPENING	OVERALL TOP OF FRAME	FRAME DEPTH	LOAD DUTY
(MM)	(MM)	(MM)	
600 x 600	665 x 665	105	Heavy duty

FEATURES

✓ Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code	C291X/060060
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	44 tn
Load duty	Heavy duty
Slow moving wheel load (pneumatic tyres)	11.5



Tel: 01543 440 440

wrekinproducts.com

Standards, classes and groupings

Wrekin loading code	Х	
Dimensions		
Frame shape	Rectangular	
Manhole shape	Rectangular	
Overall frame (A x B)		
Overall top of frame (A x B)	665 mm x 665 mm	
Clear opening (C x D)	600 mm x 600 mm	
Frame depth (E)	105mm	
Base opening (F x G)		

Overall base of frame

740 mm x 665 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.

- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>





Tel: 01543 440 440

wrekinproducts.com