

# C291X/060060

Steel Block Paviour Access Cover, 600mm x 600mm clear opening, 100mm tray depth, Loading code X



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	665 x 665	105	Heavy duty

### **FEATURES**

→ Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

### **SPECIFICATION**

#### **General information**

**Stock code** C291X/060060

Primary material Steel

**Category** Access cover

Flanges 4

Gross laden vehicle weight 44 tn

Load duty Heavy duty

Slow moving wheel load (pneumatic tyres) 11.5





## Standards, classes and groupings

Wrekin loading code X

**Dimensions** 

Frame shape Rectangular

Manhole shape Rectangular

Overall top of frame (A x B) 665 mm x 665 mm

Clear opening (C x D) 600 mm x 600 mm

Frame depth (E) 105mm

Overall base of frame 740 mm x 665 mm

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the knowledge base.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







