

C291M/060045/D4

Steel Block Paviour Access Cover, double seal, 600mm x 450mm clear opening, 100mm tray depth, Loading code M



CLEAR OPENING	OVERALL TOP OF FRAME	FRAME DEPTH	LOAD DUTY
(MM)	(MM)	(MM)	
600 x 450	655 x 505	132	Light / medium duty

FEATURES

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

SPECIFICATION

General information

Stock code	C291M/060045/D4
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal



Tel: 01543 440 440

wrekinproducts.com

Standards, classes and groupings

Wrekin loading code	М
Dimensions	
Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	
Overall top of frame (A x B)	505 mm x 655 mm
Clear opening (C x D)	600 mm x 450 mm
Frame depth (E)	132mm
Base opening (F x G)	

Overall base of frame

585 mm x 655 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.

2. It is the responsibility of all users to satisfy themselves the above data is current.

3. Installation details are available on request.

4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>





Tel: 01543 440 440

wrekinproducts.com