

# C291M/060045/D4

Steel Block Paviour Access Cover, double seal, 600mm x 450mm clear opening, 100mm tray depth, Loading code M



| CHARACTERISTIC            | VALUE               |
|---------------------------|---------------------|
| Clear opening (mm)        | 600 x 450           |
| Overall top of frame (mm) | 655 x 505           |
| Frame depth (mm)          | 132                 |
| Load duty                 | Light / medium duty |

# **SPECIFICATION**

#### **GENERAL INFORMATION**

| Stock code                 | C291M/060045/D4     |
|----------------------------|---------------------|
| Primary material           | Steel               |
| Category                   | Access cover        |
| Flanges                    | 4                   |
| Gross laden vehicle weight | 10 tn               |
| Load duty                  | Light / medium duty |
| Slow moving wheel load     | 2.5                 |
| (pneumatic tyres)          |                     |
| Seal type                  | Double seal         |
|                            |                     |

### STANDARDS, CLASSES AND GROUPINGS

| DIMENSIONS                   |                 |
|------------------------------|-----------------|
| Frame shape                  | Rectangular     |
| Manhole shape                | Rectangular     |
| Overall top of frame (A x B) | 505 mm x 655 mm |
| Clear opening (C x D)        | 600 mm x 450 mm |
| Frame depth (E)              | 132mm           |

585 mm x 655 mm

М

# **FEATURES**

Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com



Wrekin loading code

Overall base of frame





- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance.
- Installation details are available in the <u>knowledge base</u>.

  All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>.

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com





