

## C291M/060045/D4

Steel Block Paviour Access Cover, double seal, 600mm x 450mm clear opening, 100mm tray depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 450	655 x 505	132	Light / medium duty

## FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Keyway lifting points are provided on the frame for safe handling.

## SPECIFICATION

### General information

Stock code	C291M/060045/D4
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal

## Standards, classes and groupings

Wrekin loading code M

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall top of frame (A x B)	505 mm x 655 mm
Clear opening (C x D)	600 mm x 450 mm
Frame depth (E)	132mm
Overall base of frame	585 mm x 655 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

