

C291M/060060/D4

Steel Block Paviour Access Cover, double seal, 600mm x 600mm clear opening, 100mm tray depth, Loading code M

CHARACTERISTIC	VALUE
Clear opening (mm)	600 × 600
Overall top of frame (mm)	655 x 655
Frame depth (mm)	132
Load duty	Light / medium duty

SPECIFICATION

GENERAL INFORMATION

Stock code	C291M/060060/D4
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load	2.5
(pneumatic tyres)	
Seal type	Double seal

STANDARDS, CLASSES AND GROUPINGS

Wrekin loading code	М	

DIMENSIONS

Frame shape	Rectangular
Manhole shape	Rectangular
Overall top of frame (A x B)	655 mm x 655 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	132mm
Overall base of frame	735 mm x 655 mm

FEATURES

Hot dipped galvanised for corrosion resistance.

 Keyway lifting points are provided on the frame for safe handling.









- Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior ► notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- All values stated are nominal within 2.5% tolerance. ►
- ►
- Installation details are available in the <u>knowledge base</u>. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>. ►

Tel: 01543 440 440 Fax: 01543 440 444 info@wrekinproducts.com wrekinproducts.com







