

DMS0B2/7620/KGF

B125 Cover 750 x 720 x 50 Solid Top Lid Only ESB

RANGE CLEAR OPENING OVERALL FRAME FRAME DEPTH (MM) (MM)

FEATURES

Features an LPCB Level 3 lock, offering an unrivalled level of high security.

SPECIFICATION

General information

Stock code DMS0B2/7620/KGF

Primary material Ductile iron

Category Manhole cover

Flanges 4

Standards, classes and groupings

Standards BS EN 124-2

BS EN 124 Class B125

BS EN 124 Group 2

Third party certified Kitemark





Dimensions

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak [®] rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak [®] rapid curing polyester resin mortar

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the knowledge base.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







