

TWKIT/A5/3823/M

Tristar D400 surface box 380mm x 230mm clear opening with 125mm frame depth badged M (Meter) comes with one 6.5kg tub of UniPak Mortar



RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)
Tristar	380 x 230	490 x 345	125

SUPERSEDED BY

STOCK CODE	RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)
DBS0A5/3823/KT	Tristar	380 x 235	505 x 355	125

FEATURES

- ✓ Indexed corners ensure correct orientation first time, every time.

SPECIFICATION

General information

Stock code	TWKIT/A5/3823/M
Primary material	Ductile iron
Range	Tristar
Category	Surface box
Flanges	4

Standards, classes and groupings

Standards	BS EN 124-2 BS750 BS5834
BS EN 124 Class	D400
BS EN 124 Group	4
Third party certified	Kitemark
BS 5834 Grade	A
BS 750 Grade	A

Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	490 mm x 345 mm
Clear opening (C x D)	380 mm x 230 mm
Frame depth (E)	125mm
Base opening (F x G)	390 mm x 240 mm

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U6.5	6.5Kg Unipak [®] rapid curing polyester resin mortar
KEYSLIGHT	Small cover lifting keys with a standard handle (sold as a pair)

STOCK CODE	DESCRIPTION
KEY/LONG	Large cover lifting keys with a long handle (sold as a pair)

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the [knowledge base](#).
- 4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

