

PMS1 M2/45D

Safeseal A15 polypropylene manhole cover 450mm diameter clear opening with 40mm frame depth



CHARACTERISTIC	VALUE
Range	Safeseal
Overall frame (mm)	
Clear opening (mm)	Ø 450
Frame depth (mm)	40
Options	<ul style="list-style-type: none"> ▶ Neoprene seal ▶ Pressure relief holes

SPECIFICATION

GENERAL INFORMATION

Stock code	PMS1M2/45D
Primary material	Plastic
Range	Safeseal
Category	Manhole cover
Flanges	4

STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
BS EN 124 Class	A15

DIMENSIONS

Frame shape	Circular
Manhole shape	Circular
Clear opening (C x D)	Ø 450 mm
Frame depth (E)	40mm

FEATURES

- ✓ Labyrinth seal helps to prevent odour escapes and water ingress.

AVAILABLE OPTIONS

✓ **Neoprene seal**

A neoprene seal can be included to reduce ingress and egress of dirt and gasses from the chamber.

✓ **Pressure relief holes**

Pressure relief holes provide additional airflow, with sizes permitted up to the maximum allowances specified in BS EN 124.

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U12.5	12.5Kg Unipak [®] rapid curing polyester resin mortar
YPCR/U25	25Kg Unipak [®] rapid curing polyester resin mortar

- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).