

## PMS1M2/45D

Safeseal A15 polypropylene manhole cover 450mm diameter clear opening with 40mm frame depth



| RANGE    | OVERALL FRAME (MM) | CLEAR OPENING (MM) | FRAME DEPTH (MM) | OPTIONS   |
|----------|--------------------|--------------------|------------------|---|
| Safeseal |                    | Ø 450              | 40               | <input type="checkbox"/> Neoprene seal<br><input type="checkbox"/> Pressure release holes |

## FEATURES

- ✓ Labyrinth seal helps to prevent odour escapes and water ingress.

## SPECIFICATION

### General information

|                  |               |
|------------------|---------------|
| Stock code       | PMS1M2/45D    |
| Primary material | Plastic       |
| Range            | Safeseal      |
| Category         | Manhole cover |
| Flanges          | 4             |

### Standards, classes and groupings

|                 |             |
|-----------------|-------------|
| Standards       | BS EN 124-2 |
| BS EN 124 Class | A15         |

## Dimensions

|                       |          |
|-----------------------|----------|
| Frame shape           | Circular |
| Manhole shape         | Circular |
| Clear opening (C x D) | Ø 450 mm |
| Frame depth (E)       | 40mm     |

## AVAILABLE OPTIONS

### ✓ Neoprene seal

A neoprene seal can be included to reduce ingress and egress of dirt and gasses from the chamber.

### ✓ Pressure release holes

Pressure release holes provide additional airflow, with sizes permitted up to the maximum allowances specified in BS EN 124.

## ACCESSORIES

| STOCK CODE         | DESCRIPTION  |
|--------------------|--|
| PC/UNIFORM/151076  | Uniform chamber adjustment unit 760mm x 100mm x 15mm           |
| PC/UNIFORM/251076  | Uniform chamber adjustment unit 760mm x 100mm x 25mm           |
| PC/UNIWEDGE/755012 | Uniform support wedge 120mm x 50mm x 75mm                      |
| YPCR/U12.5         | 12.5Kg Unipak <sup>®</sup> rapid curing polyester resin mortar |
| YPCR/U25           | 25Kg Unipak <sup>®</sup> rapid curing polyester resin mortar   |

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)