

## C263N/170710/BT

Concrete Infill Cover, 1705mm x 710mm clear opening, 46mm frame depth, 43mm cover depth, BT Approved



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY	OPTIONS
1,705 x 710		46		<input type="checkbox"/> Standard badging

## FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- ✓ Can be installed by a single person, providing labour cost savings.

## SPECIFICATION

### General information

Stock code	C263N/170710/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3

## Standards, classes and groupings

Standards	BS EN 124-2
BS EN 124 Class	B125
BS EN 124 Group	2

## Dimensions

Frame shape	Rectangular
Overall frame (A x B)	
Clear opening (C x D)	1,705 mm x 710 mm
Frame depth (E)	46mm
Base opening (F x G)	
Overall base of frame	802 mm x 1,797 mm

## AVAILABLE OPTIONS

### ✓ Industry standard badging

Integral industry-standard badging e.g. SW (Storm Water) and FW (Foul Water). Details are taken at point of order.

## NOTES

- Supplied ready filled with concrete • Third party certified by BSI
- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

PM 32898

EMS 758038