

## C263N/232074/BT

Concrete Infill Cover, 2319mm x 742mm clear opening, 46mm frame depth, 43mm cover depth, BT Approved



CHARACTERISTIC	VALUE
Clear opening (mm)	2,319 x 742
Overall top of frame (mm)	
Frame depth (mm)	46
Load duty	
Options	► Standard badging

## SPECIFICATION

### GENERAL INFORMATION

Stock code	C263N/232074/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	3

### STANDARDS, CLASSES AND GROUPINGS

Standards	BS EN 124-2
BS EN 124 Class	B125
BS EN 124 Group	2

### DIMENSIONS

Frame shape	Rectangular
Clear opening (C x D)	2,319 mm x 742 mm
Frame depth (E)	46mm
Overall base of frame	834 mm x 2,411 mm

## FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach.
- ✓ Can be installed by a single person, providing labour cost savings.

## AVAILABLE OPTIONS

### ✓ Industry standard badging

Integral industry-standard badging e.g. SW (Storm Water) and FW (Foul Water). Details are taken at point of order.

## NOTES

- Supplied ready filled with concrete • Third party certified by BSI
- ▶ Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ All values stated are nominal within 2.5% tolerance.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#).