

## FasTrack 609<sup>®</sup> Orange

FasTrack 609 orange woven geotextile, 1500N, 75g/m<sup>2</sup> - 4.5m x 100m roll



UK  
CA CE

### DESCRIPTION

FasTrack 609 orange woven geotextile, 1500N, 75g/m<sup>2</sup> - 4.5m x 100m roll

## SPECIFICATION

### General information

Stock code	GTSG/FASTRACK/609/O
Range	FasTrack
Third party certified	UKCA CE
Roll sizes	4.5m x 100m
Geotextile product range	FasTrack

### Geotextile properties

Material		Polypropylene
Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	10kN/m
Elongation at max load (MD)	EN ISO 10319	25%
Elongation at max load (CMD)	EN ISO 10319	25%
Static puncture resistance	EN ISO 12236	1.5kN
Dynamic perforation resistance	EN ISO 13433	19mm

<b>CBR puncture resistance</b>	EN ISO 12236	1500N
<b>Dynamic cone drop</b>	EN ISO 13433	19mm
<b>Water permeability</b>	EN ISO 11058	16L/m <sup>2</sup> .s
<b>Characteristic opening size</b>	EN ISO 12956	300µm
<b>Weight</b>	EN ISO 9864	75g/m <sup>2</sup>

## NOTES

This product is suitable for high visibility and its bright colour alerts excavators of potential dangers.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

