

MultiTrack NW 20

MultiTrack NW 20 Nonwoven Geotextile, 3100N, 235g/m² - 5.25m x 100m roll



UK CE

DESCRIPTION

MultiTrack NW 20 Nonwoven Geotextile, 3100N, 235g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTNW/20
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	20kN/m
Tensile strength (CMD)	EN ISO 10319	20kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	3.1kN
Dynamic perforation resistance	EN ISO 13433	16mm
CBR puncture resistance	EN ISO 12236	3100N

Dynamic cone drop	EN ISO 13433	16mm
Water permeability	EN ISO 11058	65L/m ² .s
Characteristic opening size	EN ISO 12956	70µm
Thickness under 2kPa	EN ISO 9863-1	1.4mm
Weight	EN ISO 9864	235g/m ²

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

