

MultiTrack SNW 120

MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N, 1000g/m² - 5.25m x 35m roll



UK CE

DESCRIPTION

MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N, 1000g/m² - 5.25m x 35m roll

SPECIFICATION

General information

Stock code	GTSNW/120
Range	MultiTrack
Third party certified	CE UKCA
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	70kN/m
Tensile strength (CMD)	EN ISO 10319	70kN/m
Elongation at max load (MD)	EN ISO 10319	70%
Elongation at max load (CMD)	EN ISO 10319	70%
Static puncture resistance	EN ISO 12236	11.5kN
CBR puncture resistance	EN ISO 12236	11500N
Dynamic cone drop	EN ISO 13433	0mm
Water permeability	EN ISO 11058	20L/m ² .s

NOTES

Product may be subject to longer lead times, contact the Wrekin Geosynthetics team for details.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

