

MultiTrack SNW 80

MultiTrack SNW 80 Superior Nonwoven Geotextile, 8000N, 650g/m² - 5.25m x 50m roll



UK CE

DESCRIPTION

MultiTrack SNW 80 Superior Nonwoven Geotextile, 8000N, 650g/m² - 5.25m x 50m roll

SPECIFICATION

General information

Stock code	GTSNW/80
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 50m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	45kN/m
Tensile strength (CMD)	EN ISO 10319	45kN/m
Elongation at max load (MD)	EN ISO 10319	65%
Elongation at max load (CMD)	EN ISO 10319	70%
Static puncture resistance	EN ISO 12236	8kN
Dynamic perforation resistance	EN ISO 13433	2mm
CBR puncture resistance	EN ISO 12236	8000N

Dynamic cone drop	EN ISO 13433	2mm
Water permeability	EN ISO 11058	30L/m ² .s
Characteristic opening size	EN ISO 12956	65µm
Thickness under 2kPa	EN ISO 9863-1	4.8mm
Weight	EN ISO 9864	650g/m ²

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

