


C211MP/060060PSF

Pressed Steel Access Cover, 600mm x 600mm clear opening, 25mm depth, Loading code M+



| CLEAR OPENING (MM) | OVERALL TOP OF FRAME (MM) | FRAME DEPTH (MM) | LOAD DUTY |
|--------------------|---------------------------|------------------|---------------------|
| 600 x 600 | 625 x 625 | 25 | Light / medium duty |

FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Keyway lifting points are provided on the frame for safe handling.
- ✓ Covers are supplied with built in concealed lifting handles for cover removal without the need for manhole keys or tools.

SPECIFICATION

General information

| | |
|--|---------------------|
| Stock code | C211MP/060060PSF |
| Primary material | Steel |
| Category | Access cover |
| Flanges | 4 |
| Gross laden vehicle weight | 17.5 |
| Load duty | Light / medium duty |
| Slow moving wheel load (pneumatic tyres) | 4.25 |
| Seal type | Single seal |

Standards, classes and groupings

Wrekin loading code M+

Dimensions

Frame shape Rectangular
Overall top of frame (A x B) 625 mm x 625 mm
Clear opening (C x D) 600 mm x 600 mm
Frame depth (E) 25mm

Base opening (F x G)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

