


## C211K/030030PSF

Pressed Steel Access Cover, 300mm x 300mm clear opening, 26mm depth, Loading code K



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
300 x 300	325 x 325	26	Pedestrian

## FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Keyway lifting points are provided on the frame for safe handling.
- ✓ Covers are supplied with built in concealed lifting handles for cover removal without the need for manhole keys or tools.

## SPECIFICATION

### General information

Stock code	C211K/030030PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	2.5 tn
Load duty	Pedestrian
Seal type	Single seal

## Standards, classes and groupings

Wrekin loading code K

## Dimensions

Frame shape	Rectangular
Overall top of frame (A x B)	325 mm x 325 mm
Clear opening (C x D)	300 mm x 300 mm
Frame depth (E)	26mm

## Base opening (F x G)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

