

## C236N/228071/BT

Recessed cover for block paving, 2285mm x 710mm clear opening, 86mm frame depth, Wrekin loading code N, BT Approved



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
2,285 x 710	2,360 x 783	86	

## FEATURES

- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Can be installed by a single person, providing labour cost savings.

## SPECIFICATION

### General information

Stock code	C236N/228071/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	6
Chamber ref	10

## Standards, classes and groupings

<b>BS EN 124 Class</b>	B125
<b>Wrekin loading code</b>	N

## Dimensions

<b>Frame shape</b>	Rectangular
<b>Overall top of frame (A x B)</b>	783 mm x 2,360 mm
<b>Clear opening (C x D)</b>	2,285 mm x 710 mm
<b>Frame depth (E)</b>	86mm
<b>Overall base of frame</b>	870 mm x 2,445 mm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

