


## C271M/067067

Steel Recessed Access Cover, double seal and locked, 675mm x 675mm clear opening, 58mm tray depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
675 x 675	760 x 760	58	Light / medium duty

## KEY FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.

## SPECIFICATION

### General information

Stock code	C271M/067067
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal

## Standards, classes and groupings

Wrekin loading code M

## Dimensions

Frame shape Rectangular

Overall top of frame (A x B) 760 mm x 760 mm

Clear opening (C x D) 675 mm x 675 mm

Frame depth (E) 58mm

Base opening (F x G)

## ACCESSORIES

STOCK CODE	DESCRIPTION
KEYSRECESSED	Recessed cover lifting keys (sold as a pair)

## NOTES

Full loading capability is achieved when fully filled with grade C25 concrete

Mild steel - Galvanised to BS EN ISO 1461

Locking screws - Countersunk, slotted, M8 x 45 mm long

Unlocking - Flathead screwdriver

Lifting keys - Wire J-shaped key (Wrekin product code KEYSRECESSED)

The vertical top edge of the cover will accept up to a 12 mm tile

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

