
C271M/090075


Steel Recessed Access Cover, double seal and locked, 900mm x 750mm clear opening, 58mm tray depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
900 x 750	985 x 835	58	Light / medium duty

KEY FEATURES

- Hot dipped galvanised for corrosion resistance.



SPECIFICATION

General information

Stock code	C271M/090075
Primary material	Steel
Category	Access cover
Flanges	4

Standards, classes and groupings

Wrekin loading code	M

Steel-specific product data

Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal

Dimensions

Frame shape	Rectangular
Overall top of frame (A x B)	835 mm x 985 mm
Clear opening (C x D)	900 mm x 750 mm
Frame depth (E)	58mm
Base opening (F x G)	

Tel: 01543 440 440
wrekinproducts.com

ACCESSORIES

STOCK CODE	DESCRIPTION
KEYSRECESSED	Recessed cover lifting keys (sold as a pair)

NOTES

Full loading capability is achieved when fully filled with grade C25 concrete

Mild steel - Galvanised to BS EN ISO 1461

Locking screws - Countersunk, slotted, M8 x 45 mm long

Unlocking - Flathead screwdriver

Lifting keys - Wire J-shaped key (Wrekin product code KEYSRECESSED)

The vertical top edge of the cover will accept up to a 12 mm tile

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our Terms and Conditions of Sale



Tel: 01543 440 440

wrekinproducts.com