

### C291M/045045

Steel Recessed Access Cover, 450mm x 450mm clear opening, 100mm tray depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
450 x 450	490 x 490	105	Light / medium duty

### **KEY FEATURES**

→ Hot dipped galvanised for corrosion resistance.

Keyway lifting points are provided on the frame for safe handling.

# **SPECIFICATION**

#### **General information**

**Stock code** C291M/045045

Primary material Steel

**Category** Access cover

Flanges 4

Gross laden vehicle weight 10 tn

**Load duty** Light / medium duty

Slow moving wheel load (pneumatic tyres) 2.5





## Standards, classes and groupings

Wrekin loading code M

**Dimensions** 

Frame shape Rectangular

Overall top of frame (A x B) 490 mm x 490 mm

Clear opening (C x D) 450 mm x 450 mm

Frame depth (E) 105mm

Base opening (F x G)

Overall base of frame 580 mm x 490 mm

# **ACCESSORIES**

STOCK CODE	DESCRIPTION
KEYSHEAVY	Large cover lifting keys with a standard handle (sold as a pair)

### **NOTES**

Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy-duty key (product code KEYSHEAVY)





- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







