

FasTrack 1800

Polypropylene Woven Geotextile, 1900N, 85g/m² - 4.5m x 100m roll



PRODUCT NAME	DESCRIPTION
FasTrack 1800	Polypropylene Woven Geotextile, 1900N, 85g/m ² - 4.5m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	12kN/m
Elongation at max load (MD)	EN ISO 10319	25%
Elongation at max load (CMD)	EN ISO 10319	25%
Static puncture resistance	EN ISO 12236	1.9kN
Dynamic perforation resistance	EN ISO 13433	18mm
CBR puncture resistance	EN ISO 12236	1900N
Dynamic cone drop	EN ISO 13433	18mm
Water permeability	EN ISO 11058	18L/m ² .s
Characteristic opening size	EN ISO 12956	200µm
Weight	EN ISO 9864	85g/m ²
Roll width		4.5m
Roll length		100m

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.

