

## MultiTrack SNW 120

Superior Nonwoven Geotextile, 11500N, 1000g/m<sup>2</sup> - 5.25m x 35m roll



UK  
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 120	Superior Nonwoven Geotextile, 11500N, 1000g/m <sup>2</sup> - 5.25m x 35m roll

## Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	70kN/m
Tensile strength (CMD)	EN ISO 10319	70kN/m
Elongation at max load (MD)	EN ISO 10319	70%
Elongation at max load (CMD)	EN ISO 10319	70%
CBR puncture resistance	EN ISO 12236	11500N
Dynamic cone drop	EN ISO 13433	0mm
Water permeability	EN ISO 11058	20L/m <sup>2</sup> .s
Characteristic opening size	EN ISO 12956	55µm
Thickness under 2kPa	EN ISO 9863-1	6.5mm
Weight	EN ISO 9864	1000g/m <sup>2</sup>
Roll width		5.25m
Roll length		35m
Roll diameter		54cm

## Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.

2. It is the responsibility of all users to satisfy themselves the above data is current.

3. Installation details are available on request.

