

MultiTrack SNW 25 UV

Superior Nonwoven Geotextile, 2500N, 200g/m² - 4.4m x 100m roll



UK
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 25 UV	Superior Nonwoven Geotextile, 2500N, 200g/m ² - 4.4m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	14kN/m
Tensile strength (CMD)	EN ISO 10319	14kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	18mm
CBR puncture resistance	EN ISO 12236	2500N
Dynamic cone drop	EN ISO 13433	18mm
Water permeability	EN ISO 11058	80L/m ² .s
Characteristic opening size	EN ISO 12956	100µm
Thickness under 2kPa	EN ISO 9863-1	1.8mm
Weight	EN ISO 9864	200g/m ²
Roll width		4.4m
Roll length		100m

Roll diameter

43cm

Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.



FM32898

