

## MultiTrack SNW 31 UV

Superior Nonwoven Geotextile, 3100N, 250g/m<sup>2</sup> - 4.4m x 100m roll



UK  
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 31 UV	Superior Nonwoven Geotextile, 3100N, 250g/m <sup>2</sup> - 4.4m x 100m roll

## Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	17.8kN/m
Tensile strength (CMD)	EN ISO 10319	17.8kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	13mm
CBR puncture resistance	EN ISO 12236	3100N
Dynamic cone drop	EN ISO 13433	13mm
Water permeability	EN ISO 11058	70L/m <sup>2</sup> .s
Characteristic opening size	EN ISO 12956	95µm
Thickness under 2kPa	EN ISO 9863-1	2.2mm
Weight	EN ISO 9864	250g/m <sup>2</sup>
Roll width		4.4m
Roll length		100m

Roll diameter

50cm

## Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.



FM32898

