

MultiTrack SNW 40 UV

Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll



UK
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 40 UV	Superior Nonwoven Geotextile, 4000N, 300g/m ² - 5.25m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	22kN/m
Tensile strength (CMD)	EN ISO 10319	22kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	12mm
CBR puncture resistance	EN ISO 12236	4000N
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	60L/m ² .s
Characteristic opening size	EN ISO 12956	90µm
Thickness under 2kPa	EN ISO 9863-1	2.4mm
Weight	EN ISO 9864	300g/m ²
Roll width		5.25m
Roll length		100m

Roll diameter

54cm

Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.



FM32898

