

MultiTrack SNW 46

Superior Nonwoven Geotextile, 4600N, 370g/m² - 5.25m x 100m roll



UK
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 46	Superior Nonwoven Geotextile, 4600N, 370g/m ² - 5.25m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	27kN/m
Tensile strength (CMD)	EN ISO 10319	27kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	10mm
CBR puncture resistance	EN ISO 12236	4600N
Dynamic cone drop	EN ISO 13433	10mm
Water permeability	EN ISO 11058	65L/m ² .s
Characteristic opening size	EN ISO 12956	85µm
Thickness under 2kPa	EN ISO 9863-1	2.8mm
Weight	EN ISO 9864	370g/m ²
Roll width		5.25m
Roll length		100m

Roll diameter

57cm

Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.



FM32898

