

## MultiTrack SNW 50

Superior Nonwoven Geotextile, 5000N, 400g/m<sup>2</sup> - 5.25m x 50m roll



UK  
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 50	Superior Nonwoven Geotextile, 5000N, 400g/m <sup>2</sup> - 5.25m x 50m roll

## Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	30kN/m
Tensile strength (CMD)	EN ISO 10319	30kN/m
Elongation at max load (MD)	EN ISO 10319	55%
Elongation at max load (CMD)	EN ISO 10319	60%
Dynamic perforation resistance	EN ISO 13433	9mm
CBR puncture resistance	EN ISO 12236	5000N
Dynamic cone drop	EN ISO 13433	9mm
Water permeability	EN ISO 11058	50L/m <sup>2</sup> .s
Characteristic opening size	EN ISO 12956	80µm
Thickness under 2kPa	EN ISO 9863-1	3mm
Weight	EN ISO 9864	400g/m <sup>2</sup>
Roll width		5.25m
Roll length		50m

Roll diameter

41cm

## Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.



FM32898

