

## C221K/060060PSF

Double Seal Pressed Steel Access Cover, 600mm x 600mm clear opening, 25mm depth, Loading code K



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	630 x 630	25	Pedestrian

## KEY FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers are supplied with built in concealed lifting handles for cover removal without the need for manhole keys or tools.
- ✓ Keyway lifting points are provided on the frame for safe handling.

## SPECIFICATION

### General information

Stock code	C221K/060060PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	2.5 tn
Load duty	Pedestrian
Seal type	Double seal

## Standards, classes and groupings

**Wrekin loading code** K

## Dimensions

<b>Frame shape</b>	Rectangular
<b>Overall top of frame (A x B)</b>	630 mm x 630 mm
<b>Clear opening (C x D)</b>	600 mm x 600 mm
<b>Frame depth (E)</b>	25mm
<b>Base opening (F x G)</b>	

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

