

MultiTrack SNW 90

Superior Nonwoven Geotextile, 9000N, 780g/m² - 5.25m x 50m roll



UK
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack SNW 90	Superior Nonwoven Geotextile, 9000N, 780g/m ² - 5.25m x 50m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	54kN/m
Tensile strength (CMD)	EN ISO 10319	54kN/m
Elongation at max load (MD)	EN ISO 10319	70%
Elongation at max load (CMD)	EN ISO 10319	70%
Dynamic perforation resistance	EN ISO 13433	1mm
CBR puncture resistance	EN ISO 12236	9000N
Dynamic cone drop	EN ISO 13433	1mm
Water permeability	EN ISO 11058	28L/m ² .s
Characteristic opening size	EN ISO 12956	60µm
Thickness under 2kPa	EN ISO 9863-1	5.2mm
Weight	EN ISO 9864	780g/m ²
Roll width		5.25m
Roll length		50m

Roll diameter

58cm

Notes

1. Other grades are available on request
2. Other roll sizes are available on request

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.

