

FasTrack 60/60

Polypropylene Woven Geotextile, 5600N, 258g/m² - 5.25m x 100m roll



PRODUCT NAME	DESCRIPTION
FasTrack 60/60	Polypropylene Woven Geotextile, 5600N, 258g/m ² - 5.25m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	60kN/m
Tensile strength (CMD)	EN ISO 10319	60kN/m
Elongation at max load (MD)	EN ISO 10319	12%
Elongation at max load (CMD)	EN ISO 10319	10%
Static puncture resistance	EN ISO 12236	5.6kN
Dynamic perforation resistance	EN ISO 13433	12mm
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	18L/m ² .s
Characteristic opening size	EN ISO 12956	280µm
Thickness under 2kPa	EN ISO 9863-1	1.2mm
Weight	EN ISO 9864	258g/m ²
Roll width		5.25m
Roll length		100m

Roll diameter

33cm

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.

