

## C261N/232074/BT

BT Approved Steel Recessed Access Cover, 2319mm x 742mm clear opening, 43mm tray depth, 46mm frame depth, Loading code N



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
2,319 x 742		46	

### **KEY FEATURES**

- Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- → Hot dipped galvanised for corrosion resistance.

# **SPECIFICATION**

# **General information**

Stock code C261N/232074/BT

Primary material Steel

**Category** Access cover

Flanges







## Standards, classes and groupings

BS EN 124 Class B125

Wrekin loading code N

Steel-specific product data

Number of lids 3

**Dimensions** 

Frame shape Rectangular

**Clear opening (C x D)** 742 mm x 2,319 mm

Frame depth (E) 46mm

Overall base of frame 834 mm x 2,411 mm

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>







