


## C221M/060045PSF

Double Seal Pressed Steel Access Cover, 600mm x 450mm clear opening, 25mm depth, Loading code M



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 450	630 x 480	25	Light / medium duty

## FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers are supplied with built in concealed lifting handles for cover removal without the need for manhole keys or tools.
- ✓ Keyway lifting points are provided on the frame for safe handling.

## SPECIFICATION

### General information

Stock code	C221M/060045PSF
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	10 tn
Load duty	Light / medium duty
Slow moving wheel load (pneumatic tyres)	2.5
Seal type	Double seal

## Standards, classes and groupings

Wrekin loading code M

## Dimensions

Frame shape Rectangular

Overall top of frame (A x B) 480 mm x 630 mm

Clear opening (C x D) 600 mm x 450 mm

Frame depth (E) 25mm

## Base opening (F x G)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

