

C291N/067067

Steel Block Paviour Access Cover, 675mm x 675mm clear opening, 100mm tray depth, Loading code N

| CLEAR OPENING | OVERALL TOP OF FRAME | FRAME DEPTH | LOAD DUTY |
|---------------|----------------------|-------------|------------|
| (MM) | (MM) | (MM) | |
| 675 x 675 | 740 x 740 | 105 | Heavy duty |

Ν

KEY FEATURES

Hot dipped galvanised for corrosion resistance.

SPECIFICATION

General information

| Stock code | C291N/067067 |
|--|--------------|
| Primary material | Steel |
| Category | Access cover |
| Gross laden vehicle weight | 25 tn |
| Load duty | Heavy duty |
| Slow moving wheel load (pneumatic tyres) | 5 tn |

Standards, classes and groupings



Keyway lifting points are provided on the frame for safe handling.

Dimensions

| Frame shape | Rectangular |
|------------------------------|-----------------|
| Manhole shape | Rectangular |
| Overall top of frame (A x B) | 740 mm x 740 mm |
| Clear opening (C x D) | 675 mm x 675 mm |
| Frame depth (E) | 105mm |
| Base opening (F x G) | |
| Overall base of frame | 825 mm x 740 mm |

ACCESSORIES

| STOCK CODE | DESCRIPTION |
|------------|--|
| KEYSHEAVY | Large cover lifting keys with a standard handle (sold as a pair) |

NOTES

Mild steel - Hot dip galvanised to BS EN ISO 1461

Lifting keys - Standard heavy duty key (product code KEYSHEAVY)

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>



Tel: 01543 440 440

wrekinproducts.com







Tel: 01543 440 440

wrekinproducts.com