


DBSOA4/1010

Tristar surface box 105mm x 105mm clear opening with 100mm frame depth



RANGE	OVERALL FRAME (A X B)	CLEAR OPENING (C X D)	FRAME DEPTH (E)	BASE OPENING (F X G)
Tristar	195 mm x 195 mm	105 mm x 105 mm	100 mm	150 mm x 150 mm

Key features

- ✓ Chained cover

General information

Stock code	DBSOA4/1010
Primary material	Ductile iron
Range	<u>Tristar</u>
Category	Surface box
Flanges	4

Standards, classes and groupings

Standards	BS5834
BS EN 124 Group	4

Dimensions

Frame shape	Square
Overall frame length (A)	195 mm
Overall frame width (B)	195 mm
Clear opening length (C)	105 mm
Clear opening width (D)	105 mm
Frame depth (E)	100 mm
Base opening length (F)	150 mm
Base opening width (G)	150 mm

Notes

All values stated are nominal within 2.5% tolerance.

Accessories

STOCK CODE	PRODUCT NAME	DESCRIPTION
PC/UNIFORM/151076	UniForm	UniForm packing plate 760mm x 100mm x 15mm
PC/UNIFORM/151576	UniForm	UniForm packing plate 760mm x 150mm x 15mm
PC/UNIFORM/251076	UniForm	UniForm packing plate 760mm x 100mm x 25mm
PC/UNIFORM/251576	UniForm	UniForm packing plate 760mm x 150mm x 25mm
PC/UNIFORM/451076	UniForm	UniForm packing plate 760mm x 100mm x 45mm
PC/UNIFORM/451576	UniForm	UniForm packing plate 760mm x 150mm x 45mm
PC/UNIWEDGE/755012	UniForm	UniForm support wedge 120mm x 50mm x 75mm
YPCR/U6.5	UniPak Mortar	6.5Kg UniPak rapid curing polyester resin mortar

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.

