


## DBTOA4/1515

Tristar surface box 150mm x 150mm clear opening with 100mm frame depth



RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)
Tristar	150 x 150	230 x 230	100

## SPECIFICATION

### General information

Stock code	DBTOA4/1515
Primary material	Ductile iron
Range	Tristar
Category	Surface box
Flanges	4

### Standards, classes and groupings

Standards	BS5834
BS EN 124 Group	4
BS 5834 Grade	A

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame (A x B)	230 mm x 230 mm
Clear opening (C x D)	150 mm x 150 mm
Frame depth (E)	100mm
Base opening (F x G)	155 mm x 155 mm

## ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U6.5	6.5Kg Unipak® rapid curing polyester resin mortar
KEYSLIGHT	Small cover lifting keys with a standard handle (sold as a pair)

## NOTES

This product has a Cable loop box (for telecommunications) All values stated are nominal within 2.5% tolerance.

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

