

DBTOA4/3030

Tristar surface box 300mm x 300mm clear opening with 100mm frame depth



RANGE	CLEAR OPENING (MM)	OVERALL FRAME (MM)	FRAME DEPTH (MM)
Tristar	300 x 300	380 x 380	100

SPECIFICATION

General information

Stock code DBTOA4/3030

Primary material Ductile iron

Range Tristar

Category Surface box

Flanges

Standards, classes and groupings

Standards BS5834

BS EN 124 Group 4

BS 5834 Grade





Dimensions

Frame shape Rectangular

Manhole shape Rectangular

Overall frame (A x B) 380 mm x 380 mm

Clear opening (C x D) 300 mm x 300 mm

Frame depth (E) 100mm

Base opening (F x G) 305 mm x 305 mm

ACCESSORIES

STOCK CODE	DESCRIPTION
PC/UNIFORM/151076	Uniform chamber adjustment unit 760mm x 100mm x 15mm
PC/UNIFORM/251076	Uniform chamber adjustment unit 760mm x 100mm x 25mm
PC/UNIWEDGE/755012	Uniform support wedge 120mm x 50mm x 75mm
YPCR/U6.5	6.5Kg Unipak [®] rapid curing polyester resin mortar
KEYSLIGHT	Small cover lifting keys with a standard handle (sold as a pair)

NOTES

All values stated are nominal within 2.5% tolerance.

- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available on request.
- 4. All Wrekin products are supplied subject to our <u>Terms and Conditions of Sale</u>











