



## General information

Stock code	DGHT0D6/4242/KHP
Primary material	Ductile iron
Range	<u>Highway</u>
Category	Gully grate
Flanges	3

## Standards, classes and groupings

Standards	BS EN 124 CD 534 CD 526 DMRB MCHW
BS EN 124 Class	D400
BS EN 124 Group	3 4
Third party certified	Kitemark
CD526 Hydraulic Capacity	R

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall frame length (A)	615 mm
Overall frame width (B)	545 mm
Manhole depth (C)	105 mm

**Clear opening length (C)****Clear opening width (D)** 425 mm**Frame depth (E)** 150 mm**Base opening length (F)** 450 mm**Base opening width (G)** 450 mm**Waterway area** 910 cm<sup>2</sup>

## Notes

The D400 load capability of these Group 3 products also offers the benefit of making them suitable for exposure to Group 4 traffic types.

Pedestrian friendly with a heel safe grating.

Where 3-flange D400 Gully Grate assemblies are employed, we recommend that they are installed against a kerb, not in an open highway location

All values stated are nominal within 2.5% tolerance.

## Accessories

STOCK CODE	PRODUCT NAME	DESCRIPTION
PC/UNIFORM/151076	UniForm	UniForm packing plate 760mm x 100mm x 15mm
PC/UNIFORM/151576	UniForm	UniForm packing plate 760mm x 150mm x 15mm
PC/UNIFORM/251076	UniForm	UniForm packing plate 760mm x 100mm x 25mm
PC/UNIFORM/251576	UniForm	UniForm packing plate 760mm x 150mm x 25mm
PC/UNIFORM/451076	UniForm	UniForm packing plate 760mm x 100mm x 45mm
PC/UNIFORM/451576	UniForm	UniForm packing plate 760mm x 150mm x 45mm
PC/UNIWEDGE/755012	UniForm	UniForm support wedge 120mm x 50mm x 75mm
YPCR/U12.5	UniPak Mortar	12.5Kg UniPak rapid curing polyester resin mortar

STOCK CODE	PRODUCT NAME	DESCRIPTION
YPCR/U25	UniPak Mortar	25Kg UniPak rapid curing polyester resin mortar
SCREWLIFT	ScrewLift	Manhole cover levelling system

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.

