

C262N/131061/BT

Concrete Infill Cover, 1310mm x 610mm clear opening, 46mm frame depth, 43mm cover depth, BT Approved



CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY	OPTIONS
1,310 x 610		46		<input type="checkbox"/> Integral badging

FEATURES

- ✓ Hot dipped galvanised for corrosion resistance.
- ✓ Covers have been approved for use by telecommunications companies such as Openreach and Virgin Media.
- ✓ Designed with tapered sides and centralised lifting points to allow the cover to slide out of the frame.
- ✓ Can be installed by a single person, providing labour cost savings.

SPECIFICATION

General information

Stock code	C262N/131061/BT
Primary material	Steel
Category	Access cover
Flanges	4
Number of lids	2

Standards, classes and groupings

Standards	BS EN 124-2
BS EN 124 Class	B125
BS EN 124 Group	2

Dimensions

Frame shape	Rectangular
Overall frame (A x B)	
Clear opening (C x D)	1,310 mm x 610 mm
Frame depth (E)	46mm
Base opening (F x G)	
Overall base of frame	702 mm x 1,402 mm

AVAILABLE OPTIONS

✓ Industry standard badging

Integral industry-standard badging e.g. SW (Storm Water) and FW (Foul Water). Details are taken at point of order.

NOTES

- Supplied ready filled with concrete • Third party certified by BSI
1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
 2. It is the responsibility of all users to satisfy themselves the above data is current.
 3. Installation details are available on request.
 4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)